

Ausführungen | Versions ST-49.2

Bezeichnung Description	E	L	D	Düse Nozzle		Artikel-Nr. Item-No.
	Eingang Inlet	Länge Schlauch Length hose	Schlauch Hose	hinten Rear	vorne Front	
MR ST-49.2	G1/8 AG G1/8 male	0,5 m	Ø 5x2	0,6 (3x)	0,5 (1x)	495 334 000 5
MR ST-49.2	G1/8 AG G1/8 male	2,0 m	Ø 5x2	0,6 (3x)	0,5 (1x)	495 334 002 0
MR ST-49.2	G1/8 AG G1/8 male	5,0 m	Ø 5x2	0,6 (3x)	0,5 (1x)	495 334 005 0
MR ST-49.2	G1/8 AG G1/8 male	8,0 m	Ø 5x2	0,6 (3x)	0,5 (1x)	495 334 008 0
MR ST-49.2	G1/8 AG G1/8 male	10 m	Ø 5x2	0,6 (3x)	0,5 (1x)	495 334 010 0
MR ST-49.2	G1/8 AG G1/8 male	15 m	Ø 5x2	0,6 (3x)	0,5 (1x)	495 334 015 0

Technische Daten | Specification

Durchfluss Flow rate		
Düse Nozzle	10 l/min	2,6 US gal/min
Druck Pressure	500 bar	7300 psi
Temperatur Temperature	60 °C	140 ° F

